



Daniel Bernoulli.

JANDENUL.COM

Daniel Bernoulli



DP2 Trenching and Offshore Support Vessel Subsea Rock Installation Vessel

TECHNICAL SPECS

Deadweight	5,950 ton
Rock carrying capacity	approx. 4,750 ton
Length o.a.	95 m
Breadth	22 m
Draught loaded	6.5 m
Dynamic positioning	DYNAPOS AM/AT R Class 2
Propulsion power	2 x 1,250 kW
Bow thruster power	2 x 1,250 kW
Total installed diesel power	7,670 kW
Speed	11.5 kn
Accommodation	60 persons (notation Special Purpose Ship)
Built in	2017
Max fall pipe depth	600 m
Inclined fall pipe diam.	1,800 mm
Offshore crane	AHC crane 40 t
Rock loading capacity	1 Liebherr 984 excavator (1,000 ton/h)
Optional equipment	ROV Trencher Workclass ROV A-Frame



In the Subsea Rock Installation mode, the vessel can install approx. 4,750 ton of rock in a single load by means of the excavator, conveyor belt and the fall pipe for accurate rock installation at up to 600 m water depth. Alternatively the rock can be handled through an inclined fall pipe, for secure installation against offshore structures such as jacket platforms, gravity bases or monopile foundations.